

MODELS: Fairchild 22 C7B, 2 POLM

T.C. NUMBER: ATC 483

Engine	Menasco C-4 125 hp
Fuel	30 gallons (1 in CS 9 gallons and 1 in fuselage 21 gallons)
Oil	2-1/2 gallons
No. passengers	1
Baggage	50 lbs. (Pay load includes 2 parachutes 20 lbs. each)
Standard weight	1750 lbs.
Spec. basis	Approved Type Certificate NO. 483
Serial Nos.	1500 and up manufactured prior to 7/1/35 eligible. Approval expired as of that date.

Class I equipment:

- 101. 6.50-10 wheels and tires
- 102. Propeller - wood

Class III equipment: (\*Denotes net increase)

- 301. Fairchild shock absorber strut No. 3340  
instead of Warner strut
- 302. 19x9-3 tires Net decrease 11 lbs.
- 303. Sport type landing gear with
  - (a) 6.50-10 tires 14 lbs.\*
  - (b) 19x9-3 tires (See NOTE 2) No change in weight
- 304. 8x4 tail wheel (Goodyear)
- 305. Propeller - fixed metal 24 lbs.\*
- 306. Flares 20 lbs.
- 307. Starter and battery (baggage to be  
reduced 29 lbs.) 50 lbs.

NOTE 1. Eligible with either two piece wing or the continuous spar type.  
Aircraft equipped with the old type aileron hinges without ball bearings  
also eligible with the hinges reamed out and 5/16 inch bolts installed  
instead of 1/4 inch bolts.

NOTE 2. Sport type landing gear has Vee strut fairing and wheel streamlines.  
Inspector should specify type installed.